

Bucher XPro 5 / 8 / 15



Bucher XPro 5



Bucher XPro 15

The choice for brilliant musts

The Bucher XPro is designed to process whole bunches, destemmed and / or crushed grapes as well as fermented pomace. This grape press is especially dedicated for a selection of qualitative batches.

Very easy to handle and to use, very compact, the Bucher XPro press fits easily in every winery.





Large door opening



Extraction of perforated channels



Axial filling Bucher XPro 15

Main advantages

- \cdot Single phase press: 230 V 50 Hz (or 60Hz) for Bucher XPro 5 and XPro 8 or three-phases: 400 V 50 Hz (or 60Hz) for Bucher XPro 15.
- Large 500 x 400 mm opening for Bucher XPro 5 and XPro 8 or 600 x 500 mm for Bucher XPro 15 for a total and easy filling and quick emptying of pomace.
- Axial filling in option for Bucher XPro 15.
- Closed tank with self-cleaning perforated channels (Bucher patent) to facilitate must evacuation while pressing and to get less solids.
- Watertight polyurethane membrane approved for extended contact with grapes, grape juices and wines.
- In-tank maceration made possible thanks to cap plugs located at the end of the channels.
- 2 types of programs depending on the winemaker's needs.
- Working pressure up to 2 bars.
- Must is collected in the wheel-fitted juice trough.
- Cleaning is facilitated thanks to the easy removal of the perforated channels (Bucher Vaslin patent).
- Electro-polishing of slotted channels in option.

Adapted programming

Programmable PLC thanks to an easy-to-use display screen. 2 types of programs are available: • « Automatic »: based on a series of pressing cycles, each of them composed of a pressure rising,

a pressure holding, a decompression and tank rotation(s).

• « Prim'Step »: based on a series of pressure rising by level and pressure holdings without crumbling. This program is quite adapted to "whole-berries" Cremant-type harvesting as well as red fermented berries.

Technical Characteristics

Bucher XPro	01	Crushed grape weight (kg)	Fermented grape weight (kg)	Rated power (Kw)
5	300	800	1 500	1,5
8	480	1 280	2 400	2,8
15	900	2 400	4 500	4,4
Bucher XPro	Length (mm)	Width (mm)	Height (mm)	Trough capacity (L)
5	1 835	1 000	1 320	230
8	2 485	1 000	1 320	350
15	2 830	1 250	1 630	450

Distributed by:

Bucher Vaslin

Rue Gaston Bernier – BP 70028 F - 49290 Chalonnes sur Loire Tél. +33 (0)2 41 74 50 50 Fax +33 (0)2 41 74 50 51 E-mail : commercial@buchervaslin.com

www.buchervaslin.com Your success is our priority