



## MANUAL MONOBLOC FOR BOTH CORKING AND WIRE-HOODING, CAVEABLOCK 500



Manual monobloc provides both corking and wire-hooding in a single machine. It can be used for bottling in glass containers with a diameter ranging from 55 to 115 mm and a maximum height of 375 mm.

The machine is completely manufactured with stainless steel, food-grade plastic materials, and steel alloys. All components of the machine are accessible to facilitate cleaning and maintenance, so guaranteeing long term



duration.

The machine is equipped with Safety guards and Certificate of conformity compliant to the EC regulations.

Capacity: up to 500 b/h.

#### TECHNICAL DATA

Average Throughput: 500 b/h

Type of bottle: Glass

H from 190 to 375 mm. +/-5

D from 55 to 115 mm. +/-2

Main feed tension: 380V 50Hz (customization on demand)

Auxiliary feed tension: 24V 50Hz (customization) on demand

Total power installed: 1.5 kW

Total mass of the machine: 300 Kg

#### CORKER

Cork type (champagne/straight wine cork):

- max H 52 mm
- max D 31 mm

Power installed: 1.5 kW

Cork tube capacity: 10 pcs

#### WIRE-HOODER

Type of wire-hooding:

- 4-post wire-hood with cap
- 4-post wire-hood without cap

Air feed pressure (BAR): 6