



TWIN BELT PRESS ZBP660



Twin belt press with pneumatic belt tensioner, automatic belt control, high pressure belt cleaner and brush cleaning system for the belt. The mash is applied to the belt in a uniform layer by the adjustable metering box, at the end of the pressing sequence the pomace is removed from the belt by a scraper. In combination with our WAR65 washing system, the level of the metering box is automatically supervised and controlled.

Processable materials

Apples, Pears, Quince, Blueberries, Beetroot, Carrots, Vegetables, Manioc. This represents just an example, based on different materials and a selection of fruit processed in practice.

Technical data

Scope of supply	HD-Reiniger, Kompressor, inkl. Bürstenwalzen angetrieben (oben und unten)
Height pomace ejector	810 mm
Height waste water drain	50 mm
Height juice outlet	130 mm
Connection for juice outlet	DN25
Connection for waste water	ø 75 mm



Water consumption for cleaning	10 l/min
Contact time	1,4 - 4,2 min
Belt speed	1,2 - 4,5 m/min
Juice yield	bis zu 80 %
Material	1.4301 / AISI 304
Weight	2 200 kg
Conveyor height	10 - 40 mm
Conveyor width	220 - 440 mm
Belt width	660 mm
Discharge height	1 430 mm
Height	2 110 mm
Width	1 730 mm
Length	3 720 mm
Electrical protection	16 A
Connected load	400V 50Hz (dreiphasig)
Motor rating	3,5 kW (PS)
Nominal rating kg/h	up to 3 000 kg/h

DEVICE SPECIFICATIONS

Country of origin: **Austria**

Producer warranty: **1 year**

Electric power supply: **400V 50Hz (3 fazy)**

Nominal rating kg/h: **3000 kg/h**

Juice yield: **do 80%**

Made from: **1.4301 / AISI 304**



DESTILLER

Generated on: 2025-04-23 10:24

GALLERY



DESTILLER

Destiller - Anna i Seweryn Fabijaniak
ul. Grunwaldzka 37
37-560 Pruchnik
Tel.: +48 660 143 042
E-mail: biuro@destiller.pl

Godziny pracy
Poniedziałek - piątek 8:00 - 18:00
www.destiller.pl